

BORE SIZE - 2 INCH (50.8MM)

Max Working Pressure 3000 PSI (210 Bar)



SPECIFICATIONS

Part No.	Stroke		Pin to Pin "Closed" (L)		Pin to Pin "Extended"		Rod		Rod Thread (UNF)	Pin		Ports (UNO)	Volume (Litres)		Weight (kg)
	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)		(in)	(mm)		Push	Pull	
AG2002AB	2	50.8	14.25	362.0	16.25	412.8	1.25 (1 1/4")	31.75	1"-12	1	25.4	3/4"	0.10	0.06	7.5
AG2004AB	4	101.6	16.25	412.8	20.25	514.4							0.21	0.13	8
AG2006AB	6	152.4	18.25	463.6	24.25	616.0							0.31	0.19	9
AG2008AB	8	203.2	20.25	514.4	28.25	717.6							0.41	0.25	10
AG2010AB	10	254	22.25	565.2	32.25	819.2							0.51	0.31	10.5
AG2012AB	12	304.8	24.25	616.0	36.25	920.8							0.62	0.38	11.5
AG2014AB	14	355.6	26.25	666.8	40.25	1022.4							0.72	0.44	12
AG2016AB	16	406.4	28.25	717.6	44.25	1124.0							0.82	0.50	13
AG2018AB	18	457.2	30.25	768.4	48.25	1225.6							0.93	0.56	14
AG2020AB	20	508	32.25	819.2	52.25	1327.2							1.03	0.63	14.5
AG2022AB	22	558.8	34.25	870.0	56.25	1428.8							1.13	0.69	15.5
AG2024AB	24	609.6	36.25	920.8	60.25	1530.4							1.24	0.75	16
AG2026AB	26	660.4	38.25	971.6	64.25	1632.0							1.34	0.82	17
AG2028AB	28	711.2	40.25	1022.4	68.25	1733.6							1.44	0.88	18
AG2030AB	30	762	42.25	1073.2	72.25	1835.2							1.54	0.94	19
AG2036AB	36	914.4	48.25	1225.6	84.25	2140.0							1.85	1.13	21
AG2042AB	42	1066.8	54.25	1378.0	96.25	2444.8							2.16	1.32	23.5
AG2048AB	48	1219.2	60.25	1530.4	108.25	2749.6							2.47	1.51	26

DIMENSIONAL DRAWINGS

Standard A & B Ports (Both ends)

