

## BORE SIZE - 4 INCH (101.6MM)

Max Working Pressure 3000 PSI (210 Bar)



## SPECIFICATIONS

Part No.	Stroke		Pin to Pin "Closed" (L)		Pin to Pin "Extended"		Rod		Rod Thread (UNF)	Pin		Ports (UNO)	Volume (Litres)		Weight (kg)
	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)		(in)	(mm)		Push	Pull	
AG4008AB	8	203.2	20.25	514.4	28.25	717.6	1.75 (1 3/4)	44.45	1 1/4 - 12	1	25.4	3/4"	1.65	1.33	23
AG4012AB	12	304.8	24.25	616.0	36.25	920.8							2.47	2.00	26
AG4016AB	16	406.4	28.25	717.6	44.25	1124.0							3.29	2.66	29
AG4018AB	18	457.2	30.25	768.4	48.25	1225.6							3.71	3.00	30
AG4020AB	20	508	32.25	819.2	52.25	1327.2							4.12	3.33	32
AG4024AB	24	609.6	36.25	920.8	60.25	1530.4							4.94	4.00	35
AG4028AB	28	711.2	40.25	1022.4	68.25	1733.6							5.77	4.66	28
AG4030AB	30	762	42.25	1073.2	72.25	1835.2							6.18	5.00	39
AG4036AB	36	914.4	48.25	1225.6	84.25	2140.0							7.41	5.99	44
AG4042AB	42	1066.8	54.25	1378.0	96.25	2444.8							8.65	6.99	48
AG4048AB	48	1219.2	60.25	1530.4	108.25	2749.6							9.88	7.99	53

## DIMENSIONAL DRAWINGS

Standard A & B Ports (Both ends)

